

NogaCool



NOGACOOL consists of a manifold & Loc-Line® flexible hose with a nozzle on top and a valve at the bottom, assembled on the powerful on/off Popeye magnet.

The plug attached can be replaced by a second Loc-Line® flexible hose.

NOGACOOL is supplied with a set of three nozzles: 1/16", 1/8" and 1/4".

Working conditions are as follows:

- Pressure: 2-3.4 Bar (30-50 Psi)
- Flow rate: 940 l/hour (250 gal/hour)
- Max. working temp. 170°C

Also available with magnet and manifold only (order no. MC0161).

NogaCool

NOGACOOL MC1601

SPARE PARTS



MC0161

INCLUDES: NF 0037 magnetic base
MC0156 manifold



order no.

NF0037



320N popeye magnet
top thread M5

MC0156



manifold

MC0320



324 mm flexible
Loc-Line® hose
Other dimensions
available upon request.

MC0066



Ø1.6 mm plastic nozzle
(1/16")

MC0063



Ø3.2 mm plastic nozzle
(1/8")

MC0067



Ø6.3 mm plastic nozzle
(1/4")

MC0072



Wide plastic nozzle
16 holes Ø1 mm

MC0073



Wide plastic nozzle
16 holes Ø1.5 mm